

STANDARD DEPARTURE CHART - INSTRUMENT-5

HYOGO TWO DEPARTURE

RWY 32R/32L : Climb RWY HDG to 500 FT or above, turn left within 4NM (OWE 5DME), climb via 201 DEG from OW NDB (OWE R-220) to YODOH,....

RWY 14R/14L : Climb RWY HDG to 500 FT or above, turn right, climb HDG 230 DEG to intercept and proceed via OWE R-220 (201 DEG from OW NDB) to YODOH,....

....turn right to intercept and proceed via SKE R-321 to HYOGO.

Cross SKE R-321/22DME at or above 6,000 FT.

Note 1 : OWE R-220 for RWY 32R/32L is to be utilized only during the outage of OW NDB.

Note 2 : For RWY 14R/14L, following climb gradient should be maintained until 500 FT.

Speed (Knots)	60	90	120	150	180	210
Rate (Feet/Min)	300	450	600	750	900	1050

ASAGI TRANSITION

After HYOGO, proceed via SKE R-321 to ASAGI.

Cross SKE R-321/36DME at or above 7,000 FT.

TOZAN TRANSITION

After HYOGO, proceed via SKE R-321 to TOZAN.

Cross SKE R-321/36DME at or above 7,000 FT.

