LUFTFAHRTHANDBUCH DEUTSCHLAND AIP GERMANY

STANDARD DEPARTURE

ROUTES – INSTRUMENT (SID)

		Route	After Take-Off		
	Designator		Climb to	Contact	Remarks
	1	2	3	4	5
I	MANEM 7W	MANEM SEVEN WHISKEY On track 257° to 4.0 DME MND; LT, on R 196 RID to 29.0 DME RID; RT, intercept R082 ZWN to MANEM (\triangle). Climb with 6.8% (413 ft/NM) or more until passing 600. GPS/FMS RNAV: [A800+] - FM050[L] - FM052[R] - MANEM.	5000 ft	Langen Radar 129.350	 PDG 6.8% (413 ft/NM) due to obstacles. During activity of ED-R205 (TRA) MAX FL80.
	OLIVI 3W	OLIVI THREE WHISKEY On track 257° to 6.0 DME MND; RT, on track 334° to KOSAX (\triangle); LT, on track 295° to OLIVI (\triangle). Climb with 7.9% (480 ft/NM) or more until passing 3000, then climb with 6.4% (390 ft/NM) or more until passing 6000. GPS/FMS RNAV: [A 800+] - FM053[R] - KOSAX[A6000+; L] - OLIVI.			 PDG 7.9% (480 ft/NM) due to obstacles. If unable to comply, request alternative instruction by ATC. PDG 6.4% (390 ft/NM) due to airspace structure. After 6.0 DME MND BRNAV equipment necessary. During activity of ED-R 205 (TRA) MAX FL80.
I	RINEX 2W	RINEX TWO WHISKEY On track 257° to 4.0 DME MND; LT, intercept R196 RID to 26.0 DME RID; LT, on bearing 082° inbound NKR to RINEX (△). Climb with 6.8% (413 ft/NM) or more until passing 600. Cross RINEX at 5000 or above. GPS/FMS RNAV: [A800+] - FM050[L] - <u>FM004[L]</u> - FM005 - RINEX[A5000+].			PDG 6.8% (413 ft/NM) due to obstacles.
I	ROLSO 2W	ROLSO TWO WHISKEY On track 257° to 4.0 DME MND; LT, intercept R196 RID to 26.0 DME RID; LT, on bearing 082° via RINEX (△) to NKR NDB (△); RT, on track 086° NKR to ROLSO (△). Climb with 6.8% (413 ft/NM) or more until passing 600. Cross RINEX at 5000 or above. GPS/FMS RNAV: [A800+] - FM050[L] - FM004[L] - FM005 - RINEX[A5000+] - NKR[R] - ROLSO			 PDG 6.8% (413 ft/NM) due to obstacles. Flights with destination EDDF or EDFE shall file ROLSO DCT SUPIX - T163 - PSA.
I	UMDAS 2W	UMDAS TWO WHISKEY On track 257° to 4.0 DME MND; LT, intercept R196 RID to 26.0 DME RID; LT, on bearing 082° NKR to RINEX (△); LT, on track 060° to UMDAS (△). Climb with 6.8% (413 ft/NM) or more until passing 600. Cross RINEX at 5000 or above. GPS/FMS RNAV: [A800+] - FM050[L] - <u>FM004[L]</u> - FM005 - RINEX[A5000+; L] - UMDAS.			 PDG 6.8% (413 ft/NM) due to obstacles. After RINEX BRNAV equipment necessary.
		(Sample: <u>FM004</u> fly-over waypoint)		1	1

Contact Langen Radar immediately after take-off!