

# STANDARD ARRIVAL CHART-INSTRUMENT

VAR 4° W  
 ATIS 128.45  
 APP 119.9(124.2)  
 TWR 118.3(118.85, 130.0)

ZHCC ZHENGZHOU/Xinzheng  
 RWY 30

BEARINGS ARE MAGNETIC  
 ALTITUDES, ELEVATIONS  
 AND HEIGHTS IN METERS  
 DME DISTANCES IN NAUTICAL  
 MILES  
 DISTANCES IN KM

TL 3600  
 TA 3000  
 3300(QNH ≥ 1031HPA)  
 2700(QNH ≤ 979HPA)

WEIXIAN  
 115.7 WXI  
 CH 104X  
 N36 21.8E114 55.0

TAMIX  
 N35 36.7  
 E113 23.9

TMX-11A, 12A  
 TMX-13A (by ATC)

NOPIN  
 N35 26.8  
 E113 28.3

R348°  
 D30.0CGO  
 N34 59.5  
 E113 40.4  
 2700  
 or by ATC

D30.0CGO

LEKUB  
 N35 31.4  
 E114 15.0



For Enroute Flight:  
 1. Designator for WEIXIAN VOR 'WXI'-  
 LEKUB-DUBAG is V33.

DUBAG  
 D21.5CGO  
 N34 51.8  
 E113 43.8

Ⓐ Altimeter setting may be required by ATC:  
 Aircraft from TAMIX shall descend to 2400m  
 or 2700m and keep altitude to D13.5CGO.

D13.5CGO  
 2400 or 2700  
 or by ATC

ZHENGZHOU  
 114.5 CGO  
 CH 92X  
 N34 31.1E113 50.6

IAF  
 N34 39.0  
 E114 01.3  
 1500

TMX-12A  
 WXI-12A  
 ZHO-12A


LMM  
 211 A  
 N34 30.7E113 52.2

IAF  
 D14.0CGO  
 N34 20.0  
 E114 00.9  
 1200

D30.0CGO

ZHOUKOU  
 115.5 ZHO  
 CH 102X  
 N33 39.9E114 39.3

MNM SECT ALT



Changes: Procedures.